



 Lexmark™

# Lexmark XC4352

Security and performance



# Lexmark XC4352

The Lexmark XC4352 is designed for performance, security, and ease of use for mid-to-large workgroups at speeds up to 50 ppm\*. Single-pass two-sided scanning, ultrasonic multifeed detection, and a 25 cm tablet-like touchscreen make handling your print jobs easy. Toner cartridges that yield up to 26,000/15,000 black/colour pages\*\* keep you going.

## Made to last. Easy to upgrade.

- ▶ With durable steel frames, long-life components and high-yield cartridges, printers are intentionally engineered to last seven years or more.
- ▶ Long-lasting Unison™ Toner delivers consistently outstanding print quality, reduces internal wear on long-life components, and protects the print system.
- ▶ Easily upgradeable to the latest apps and security features.



## Faster performance and ease of use

- ▶ Scanning is fast and accurate thanks to the single-pass two-sided automatic document feeder with ultrasonic multifeed detection.
- ▶ The large 25 cm, tablet-like, button-free touchscreen will help you intuitively complete every task, from the basic to the complex.
- ▶ An Intelligent Storage Drive (ISD) is standard on this model, providing faster startup, faster data retrieval and more reliability.

## Make a statement with professional colour

Enjoy the benefits of vibrant, professional-quality output allowing you to do more colour printing in-house - saves time and money. Match corporate colours on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Colour Replacement.

## Secure by design

Lexmark security features help keep your information safe - in the document, on the device, over the network and at all points in between. Our comprehensive approach to product security is a design and engineering mandate across our entire product portfolio.

## Sustainability matters

- ▶ Designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

## Power up with IoT


- ▶ Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average yield based on approximately 5% print coverage. Yield stated on cartridge labels, packaging, and printer device menu pages may be substantially lower than final ISO tested yield. For Lexmark's official statement of yield, see ISO yield reports at [https://www.lexmark.com/en\\_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html](https://www.lexmark.com/en_us/products/supplies-and-accessories/iso-page-yields/color-laser-reports.html). Update firmware on your device to ensure accuracy of displayed yield. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

# Lexmark XC4352



- 1 **Multifunction product with 25 cm touch screen**  
621 x 479 x 533 mm
- 2 **550-Sheet tray with 100-sheet multipurpose feeder**  
Dimensions included as part of base model
- 3 **550-Sheet Tray**  
119 x 463 x 483 mm
- 4 **550-Sheet Tray**  
119 x 463 x 483 mm
- 5 **550-Sheet Tray**  
119 x 463 x 483 mm

- 6 **550-Sheet Tray**  
119 x 463 x 483 mm
- 7 **Adjustable Stand**  
521 x 653 x 625 mm
- 8 **Convenience Stapler HV**  
82 x 109 x 121 mm



**P/N**  
47C9967

**Hardware**  
Lexmark XC4352

**P/N**  
24B7515

**Supplies**  
Lexmark XC4342, XC4352 Cyan 14.2K Toner Cartridge

24B7516

Lexmark XC4342, 4352 Magenta 14.2K Toner Cartridge

24B7517

Lexmark XC4342, 4352 Yellow 14.2K Toner Cartridge

24B7518

Lexmark XC4342, XC4352 Black 25K Toner Cartridge

24B7557

Lexmark XC4352 Cyan 15K Toner Cartridge

24B7558

Lexmark XC4352 Magenta 15K Toner Cartridge

24B7559

Lexmark XC4352 Yellow 15K Toner Cartridge

24B7560

Lexmark XC4352 Black 26K Toner Cartridge

71C0W00

Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container

71C0Z10

Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit

71C0Z50

Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit

**P/N**

**Paper Handling**

40C2100

550-Sheet Tray

47C4597

Convenience Stapler

**P/N**

**Memory Options**

27X0400

500+ GB Hard Disk

57X0070

Removable Hard Disk Enclosure Kit

**P/N**

**Application Solutions**

57X0300

Contact Authentication Device

57X0301

Contactless Authentication Device (Secondary Alternative)

82S1203

IPDS License

82S1204

Bar Code License

**P/N**

**Connectivity**

1021294

USB (2 Metre) Cable

27X0823

MarkNet N8370 Wireless for CS720, CS725, CX725

27X6410

Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server

57X7020

English Keyboard Kit

SPD0002

Surge Protective Device, 220-240V

**P/N**

**Furniture**

40C2300

Adjustable Stand

Supports up to four optional 550-sheet trays.

All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at [http://www.lexmark.com/publications/furniture\\_safety/](http://www.lexmark.com/publications/furniture_safety/)

## Product Specifications

## Lexmark XC4352

Printing	
Display	Lexmark e-Task 10-inch (25 cm) class colour touch screen
Print Speed	Up to: Black: 50 ppm <sup>1</sup> (A4) / Colour: 50 ppm <sup>1</sup> (A4)
Time to First Page	as fast as: Black: 5.6 seconds / Colour: 6.1 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi
Memory	Standard: 2048 MB / Maximum: 2048 MB
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk available
Recommended Monthly Page Volume	2000 - 20000 pages <sup>2</sup>
Maximum Monthly Duty Cycle	Up to: 150000 pages per month <sup>3</sup>
Copying	
Copy Speed	Up to: Black: 50 cpm <sup>1</sup> (A4) / Colour: 50 cpm <sup>1</sup> (A4)
Time to First Copy	as fast as: Black: 5.7 seconds / Colour: 6.3 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed / Duplex Scan Speed (A4/Ltr)	Up to: Black: 98 / 104 sides per minute / Colour: 98 / 104 sides per minute
A4/Ltr Simplex Scan Speed / Scan Speed (A4/Ltr)	Up to: Black: 49 / 52 sides per minute / Colour: 49 / 52 sides per minute
ADF Paper Input Capacity	Up to: 100 pages 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies <sup>4</sup>	
Laser Cartridge Yields	up to: 14,200 <sup>5</sup> -page Colour (CMY) High Yield Cartridges / up to: 25,000 <sup>5</sup> -page Black Extra High Yield Cartridge / up to: 15,000 -page Colour (CMY) High Yield Cartridges / up to: 26,000 -page Black Extra High Yield Cartridge
Imaging Unit Estimated Yield	Up to: 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage <sup>6</sup>
Cartridge(s) Shipping with Product	5,000 <sup>5</sup> -page Black and Colour (CMYK) Return Programme Toner Cartridges <sup>5</sup>
Paper Handling	
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin, 550-Sheet Input
Optional Paper Handling	550-Sheet Tray
Paper Input Capacity	Up to: Standard: 650 pages 75 gsm bond / Maximum: 2850 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 300 pages 75 gsm bond / Maximum: 300 pages 75 gsm bond
Media Types Supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information <sup>7</sup>	
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Optional Network Ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC
Noise Level	Operating: 53 dBA (Print) / 56 dBA (Copy) / 51 dBA (Scan)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 metres
Product Warranty	1-year Onsite Service + 3-years Parts Only guarantee (Maintenance Kit included)
Size / Weight	H x W x D: 621 x 479 x 533 mm / 39.5 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.69 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average yield based on approximately 5% print coverage. <sup>6</sup> Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>7</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/> (<http://www.openssl.org/>)).