

Document shredders DAHLE 506air



- Team document shredder for professional use
- Improves indoor climate even when the document shredder is used heavily. The unique DAHLE CleanTEC® filter system demonstrably reduces fine dust levels produced by document shredding.
- MHP® (Matrix High-Performance) cutting rollers: high-quality compound steel rollers for a guaranteed long service life
- Patented manufacturing process conserves resources by using significantly less raw material compared to production of traditional cutting rollers
- Higher performance thanks to MHP cutting rollers
- Door open wide for easy emptying of waste container
- Intuitive, user-friendly illuminated control panel with audio signals
- Device shuts down automatically after 30 minutes without use
- Electronic start and stop function controlled by integrated light barrier
- Automatic paper reverse function clears excess paper
- Convenient feeding and reversing function for manual control
- Automatic safety shut-off when the waste container is full or the door is open
- Optical waste level indicator
- High-quality solid steel cutting rollers made of special steel for guaranteed long lifetime
- Pull-out waste container
- Powerful motor ensures high performance and longer run times
- Extremely quiet operation
- Convenient swivel castors for greater mobility
- Easy-to-reach main switch on rear of device
- Practical cold-device plug can be detached from document shredder

Article number	51322-13847
Entry width in mm	260
Sheet capacity (80g/sqm)*	11 - 13 sheets
Particle size (in mm)	2 x 15 mm
Security levels	P-5/F-2/T-5/E-4
Autom. oiler	✓
Oil incl. in ml	400
running time	10min
CDs/DVDs	-
Cards	✓
Paper clips	✓
Waste collection volume (in l)	60
Noise level when idle (db(A))	46
Power consumption (W)	650
Dimensions H x W x D (mm)	865 x 545 x 435
EAN	4009729063637



* Maximum number of DIN A4 sheets that can be shredded in a single load under the following conditions: new cutting rollers (oiled if necessary), cold motor, power supply with rated voltage and rated frequency (230V/50Hz; 120V/60Hz). Sheet capacity may be lower and operating noise higher under different conditions. Sheet capacity may also vary due to sheet characteristics and paper feed.